

Product Sheet

GENA GREASE EP

Lithium E.P. grease for industrial and auto motive applications

Description

High quality grease with E.P. properties. Suitable for high loaded plan and roller bearings even operating at high temperatures, or as general purpose grease in order to aid product rationalization.

Specifications

Recommended, according our experience, to fulfill the following:

- ISO 6743-9 L-XBDEB 2
- DIN 51825 KP 2 K-20

Benefits

- Excellent oxidation stability, both static and dynamic
- Wide temperature range of application
- High resistance to water washout
- Outstanding corrosion protection
- Very high resistance to mechanical breakdown
- Contains E.P. additives allowing it to be used in high load applications
- Good pumpability even at low temperatures

Applications

GENA GREASE EP can be used both in Stauffer or Tecaletmit, and in centralized systems. Do not mix with different greases.

Average Typical Data

Properties	Unit	Value	Test Method
NLGI Class		2	
Appearance		Pastous	
Color		Light brown	
Worked Penetration	mm/10	265 / 295	ASTM D 217
Drop Point	°C	180	ASTM D 556
Timken OK Value	lbs.	40	ASTM D 2509
Operating temperature range	°C	-20 / +120÷140	

The information contained in this product sheet are the best of our knowledge and nothing contained therein shall be assumed as a guarantee. It is responsibility of the user to determine the suitability and correct relevance of these information according to its specific use.